

Test No:		Applicator:				Date:	
Company:					Operator:		
Weather Conditions Etc.					Nominated Film Thickness 180 Nominal i.e. 150 to 210um ÿ, 220 Nominal i.e. 190 to 250um ÿ, 300 Nominal i.e. 270 to 330um ÿ		
Paint Brand		Type		Colour	Batch No		% Thinners
Time	Test No	Run No	Stated Speed	Time (sec's)	Calc. Speed	Comments / Results	Pass / Fail
						1	
						2	
						3	
						4	
						5	
						6	
						7	
						8	
						9	
						10	
						11	
						12	
						13	
						14	
						15	
						16	
						17	
						18	
						19	
						20	
						21	
Intermittent Line				Bead Rate			
Dist.(mm)		Spacing		Delay (mm)	Painted plastizote (gms)		
1		seg.			minus plastizote (gms)		
2		gap			= Paint Weight (gms)		
3		seg			Beaded plastizote (gms)		
4		gap			minus plastizote (gms)		
5		seg			= Paint & Beads (gms)		
6		gap			minus Paint Weight (gms)		
7		seg			= Beads /500mm (24.75 to 30.25)		
				kg / km - (49.5 to 60.5)			
Straightness		Paint to Curb		P/22 Turn Arrow			
Notes:							