

CERTIFICATE OF COMPLIANCE NZTA T 12:2013

Applicator: 1998 Mitsubishi Canter / Coastline Markers Cold Applied Plastic Applicator, registration number XA4391

Type: LA CAP

Owner: Fulton Hogan Ltd, T/A Coastline Markers
P O Box 302-528
North Harbour 0751



Test Description: **The long-life pavement marking applicator described by this certificate has been tested under the conditions described and found to comply with the relevant requirements of NZTA Specification NZTA T12:2013**

Test Conditions: The scope of the NZTA T12: 2013 recertification was as follows;

1. Application of Plain Flat Cold Applied Plastic to Schedule A, Flat Spray Cold Applied Plastic in accordance with Coastline Markers Technical Specification, NZTA P30:2008 and NZTA T12:2013
Tested at 100mm, 150mm & 200mm

- Test Identification:**
- The Chassis number of the tested unit is 7AIFEI26WPA02586
 - The tests were carried out at Mitre 10 Mega Albany on the 16th/17th March 2023.
 - The materials used for the tests were:
Damar Spray Plastic Parts A & B
Potters AC-07 Type C adherence promoting coated drop-on glass beads.

Equipment Tested:	CAP Spray Guns	Handok	45794-1 & 45794-2
	CAP Pump	Graco Viscount II	45794
	Bead Applicators	Jet-Line	
	Compressor	Fusheng TA80	8830199
	Speedometer	Kadcam Autoline 200	45794

Applicator Speeds (kph)		100mm	150mm	200mm
	Schedule One	7.4	4.9	3.2

SCHEDULE A

Flat Spray Cold Applied Plastic in accordance with Coastline Markers Technical Specification, NZTA P30:2008 and NZTA T12:2013

The markings when applied to flat electro-galvanised steel plates met all dimension and performance requirements as specified in;

NZTA P30:2009 Specification for High Performance Roadmarkings and

NZTA T12:2013 Specification for Long-Life Pavement Marking Material Applicator Testing.

The values specified in NZTA P30:2009 and NZTA T12:2013 used for determination of compliance were as follows:

Gap length between segments

Where gap is 3.0m or more: $\pm 300\text{mm}$

Where gap is less than 3.0m but greater than 1.0m; $\pm 150\text{mm}$

Where gap is less than 1.0m: $\pm 50\text{mm}$

Length of segment.

Where segment is longer than 5.0m; $\pm 150\text{mm}$

Where segment is shorter than 5.0m but longer than 1.0m; $\pm 75\text{mm}$

Where segment is shorter than 1.0m; $\pm 50\text{mm}$

Line width.

All line widths; + 10 %, - 5 % of the specified value. (150 mm)

Flat Spray Cold Applied Plastic.

Dry film thickness (DFT) of $450\ \mu\text{m} \pm 75\ \mu\text{m}$.

Retroreflectivity.

AS/NZS 2009 Class B (drop-on) glass beads applied uniformly at a minimum rate of $275\text{gm}/\text{m}^2$.

Dry retroreflectivity; a minimum of $150\ \text{mcd}/\text{m}^2/\text{lux}$.

Wet retroreflectivity; a minimum of $80\ \text{mcd}/\text{m}^2/\text{lux}$

Day Time Visibility.

Minimum Qd of $100\ \text{mcd}/\text{m}^2/\text{lux}$


Colour.

White; a discolouration of not more than 4/5 from colour Y35 of AS2007S

Yellow; a discolouration of not more than 4/5 from colour Y13 – Y14 of AS2007S

Skid Resistance.

45 BPN or greater for roadmarkings with a dry film thickness of less than 0.9 mm



CERTIFICATE OF COMPLIANCE NZTA T 12:2013

Registration Details:

[NZRF Stamp & Unique Number]

5670



Initial Certificate Testing Officer:

Ross Ridings
Quality Surveillance Ltd

T/12 Testing Officer:

Lance Wright
Fulton Hogan Ltd, T/A Coastline Markers

Signed:



Date of Expiry:

17th March 2024

Copied from NZRF T 12 Register